

## Nylon PA 11 White Datasheet



### Overview

Nylon PA 11 White is a sustainable polyamide material optimized for selective laser sintering (SLS). It's suitable for creating functional components like gears, drone parts, and other technical elements designed to endure high-stress conditions.

**As-printed Part's Tolerance:  $\pm 300\mu\text{m}$  or 0.3%**

**Maximum Printing Size: 300\*200\*280mm**

## Properties

Thermal Properties	Metric	Method
Heat Deformation (0.46 MPa)	170.5°C	ASTM D648M
Heat Deformation (1.82 MPa)	85.5°C	ASTM D648M
Mechanical Properties	Metric	Method
Tensile Strength	45MPa	ASTM D638M
Tensile Modulus	1600MPa	ASTM D638M
Elongation at Break	48%	ASTM D638M
Flexural Properties	Metric	Method
Flexural Modulus	1500MPa	ASTM D790
Flexural Strength	49MPa	ASTM D790
Impact Properties	Metric	Method
Notched Impact Strength	7 J/m	ASTM D256
Unnotched impact strength	31 J/m	ASTM D256
Density Properties	Metric	Method
Density	0.98 g/cm³	DIN 53466

## Pros

Nylon PA 11 White, when 3D printed using SLS technology, delivers a combination of strong mechanical performance, flexibility, and chemical resistance. It's particularly well-suited for demanding applications in the automotive, aerospace, and medical sectors.

## Cons

This material is prone to warping and shrinkage during the printing process and often demands thorough post-processing to achieve a smooth finish. Prints made from powder-based materials typically have a rough, grain-like texture.

## Applications

Automotive Components

Custom Prosthetics and Orthoses

Gears

Electrical Connectors

Enclosures and Housings

Jigs and Fixtures

Sensor Components

Surgical Tools

Brackets and Gaskets